

# POWER-POS

## GENERAL

Type: Thermal receipt printer (80 mm)

## PRINTING PARAMETERS

Printing Method: Direct thermal per line Printing

Speed: 200 – 220 mm/s

Resolution: 576 dots/line

Print Width: 80 mm

Cutter: Automatic (full or partial cut)

Fonts:

ANK A: 12 × 24

ANK B: 9 × 17

Chinese: 24 × 24

Commands: ESC/POS

NV Flash Memory: 256 KB

## CONNECTIVITY

Interface: USB + Bluetooth + LAN + WiFi

## BARCODES

1D: UPC-A, UPC-E, EAN-13, EAN-8, Code 39, ITF, Codabar, Code 93, Code 128

2D: QR Code, PDF417

## COMPATIBILITY

Systems: Windows, Linux, Android, iOS

PAPER

Type: Thermal roll paper

Width: 79.5 ± 0.5 mm

Roll diameter: ≤ 83 mm

Thickness: 0.06 – 0.08 mm

Line spacing: 3.75 mm (adjustable)

## ELECTRICAL PARAMETERS

Adapter:

Input: AC 100 – 240V / 50–60 Hz

Output: DC 24V / 1.5A

Cash register control: 12V / 1A

## PERFORMANCE

Print lifespan: 100 km

Cutter lifespan: 1.5 million cuts

## PHYSICAL PARAMETERS

Dimensions: 130 × 160 × 122 mm Weight: 0.8 kg

## ENVIRONMENTAL PARAMETERS

Temperature:

Operating: -10°C to 45°C

Storage: -20°C to 60°C

Humidity: 10% – 90

## Model 8390BW

